


## SCODIX ULTRA2

**Series of Digital Enhancement Presses** 

The Scodix Ultra2 digital enhancement series of presses bring new levels of flexibility, quality and productivity to commercial PSPs and folding carton converters.

The Scodix Ultra2 series of presses include:

Scodix Ultra2 Scodix Ultra2 Pro Scodix Ultra2 Pro with Foil





















Edge

Sc S<sub>l</sub>

Scodix Spot

Scodi

Scodix

Scodix

Scodix

## THE ULTIMATE MULTI MATERIAL PLATFORM

Scodix Ultra2 series of presses with the multi material platform provides you with the largest array of enhancement job capabilities in the print industry today. The multi material platform produces unmatched quality – on time and on budget – all on one press platform, supporting multi applications, multi print processes and multi substrates.

The **multi applications** enable up to 9 applications to efficiently run on this single platform, replacing the need to run separate systems on your production floor.

## **Applications Include:**

Scodix Sense™Scodix Cast&Cure™Scodix Spot™Scodix Crystal™Scodix Foil ™Scodix Braille™Scodix Metallic™Scodix Glitter™Scodix VDE/VDP™

The **multi print processes** allows performing enhancements from various CMYK print processes up to B2+ size sheet format ( $545 \times 788$ mm /  $21.5 \times 31$ in), with material weights from 135 to 675gsm / 6 to 30 points and material thickness up to 0.7mm / 700 microns. Scodix Ultra2 series of presses support most CMYK print processes including: Offset, Electrolnk (HP Indigo), Inkjet and Toners.

The **multi substrates** give you the freedom to print enhancements on paper, lamination, variety of water based coatings, PVC and carton. Today, there are over 100 qualified medias including offset, digital, plastics, laminated/non-laminated, coated and uncoated with no need for additional, complex set-up. Scodix brings numerous benefits to a range of industries, including commercial print, direct mail, folding cartons, point of display, web2print, security markings and many more with a focus on fine details and surface finishing. Products produced with Scodix enhancements include business/greeting cards, folders, book covers, brochures, labels, packaging and more.

## TECHNICAL SPECIFICATIONS

| Foil technology                           | Digital in-line with Scodix PAS™ foil technology                    |
|---|---|
| Foil roll width (min/max)                 | 50-500 mm / 1.97-19.68 in   |
| Foil roll size                            | Diameter: max 30 cm; Length: max 2,000 m; Core: 77 mm / 3 in        |
| Max number of simultaneous rolls          | Up to 4 rolls   |
| Polymer layer thickness                   | From 5 up to 250 microns  |
| Substrate weight                          | 135-675 gsm / 6-30 points   |
| Substrate thickness                       | Up to 700 microns   |
| Foil film type*                           | Wide variety of industry standard hot/cold foil films               |
| Substrates**                              | Offset, digital, plastics, laminated and coated/uncoated substrates |
| Resolution                                | Up to 2,540 x 450 DPI   |
| Variable Data Enhancement (VDP)           | PDF, optimized PDF, barcode system (optional)                       |
| Scodix RSP™ technology                    | 4 CCD camera system, RSP™ (Rotation, Scale, Position) algorithm,    |
|   | automatic positioning, ±100 micron image to image registration      |
| Substrate loading sizes                   | Min - L297 x W420 mm / 11.7 x 16.5 in                               |
|   | Max - L545 x W788 mm / 21.5 x 31 in                                 |
| Printing image size                       | Max - L748 x W504 mm / 29.4 x 19.8 in                               |
| Foil station dimensions (L x H x W)       | 1660 x 1448 x 1979 mm / 65.3 x 57 x 77.9 in                         |
| Press with station dimensions (L x H x W) | 7880 x 1790 x 1979 mm / 310.2 x 70.4 x 77.9 in                      |
| Station weight (net)                      | 900 kg / 1,984 lbs.   |
| Press weight (net)                        | 4,400 kg / 9,700 lbs.   |
|   |   |

<sup>\*</sup> Based on Scodix Recommended Foil List (RFL) for foil



<sup>\*\*</sup> Based on Scodix Recommended Media List (RML) for foil where surface tension should be within range of 36-44 dyne/cm